

5	Screwdriver	Remove the 2 OEM mounting screws. These will NOT be reused.	
	Rag	Carefully pull the fuel rail and injectors from the throttle body.	
		Bring the assembly to a clean work bench. Carefully pull each injector from the fuel rail. Have a rag handy.	
6		Adapter fittings are NOT included with the fuel rail. As shown, the optional 20-1135-PK FUEL RAIL PLUMBING KIT includes all the necessary adapter fittings to reuse the OEM fuel line.	
		For custom plumbing installations, the fuel rail has four 3/4"-16 (8AN ORB) end ports. Go to www.radiumauto.com to find an array of compatible adapter fittings, regulators, pulse dampers, etc.	
7	Oil Lubrication	20-1135-PK FUEL RAIL PLUMBING KIT, KAWASAKI TERYX KRX 1000 Lubricate all O-rings and install the provided fittings in the exact fuel rail ports shown.	
	7/8" Wrench		
	5/16" Allen Wrench		
8	Oil Lubrication	There is an online misnomer that because the inlet on the OEM rail comes in on one side, there is not equal pressure sent to each fuel injector. This is not the case. However, if this something that you strongly believe, use these fittings instead of the plumbing kit above.	
	7/8" Wrench		
	5/16" Allen Wrench		
	4mm Allen Wrench		
	9/16" Wrench		
	5/8" Wrench		
9	Oil Lubrication	If by chance you do experience inconsistent fuel delivery, the best recommended solution is installing a fuel pulse damper. This can be installed into the lower center port in conjunction with the 20-1135-PK fuel rail plumbing kit, as shown. (1x) 20-0776 FPD-R, 8AN ORB	
	7/8" Wrench		
10		The fuel rail is machined to accept 11mm upper injector O-rings. It is compatible with factory (or equivalent) fuel injectors.	

11	Oil Lubrication	Lubricate the 2 fuel rail injector bores and the upper injector O-rings and push them together.	
		Optional 20-0776 fuel pulse damper shown in the lower center port.	
12	4mm Allen Wrench	Lubricate the lower injector O-rings and the corresponding intake manifold seats.	
		Lineup the fuel rail assembly to the intake manifold ports and press downward to fully seat. Properly orient the connectors, as shown.	
		Secure the rail using the provided screws.	
		Plug in the fuel injector connectors until they click in place.	
13		20-1135-PK FUEL RAIL PLUMBING KIT, KAWASAKI TERYX KRX 1000	
		Inspect the condition of the OEM fuel line connector. Clean any debris and replace any parts that may be permanently damaged.	
		Push the OEM fuel line onto the fuel rail inlet port. Push the lock down until it clicks in place. Gently give the line a tug to confirm the connection has been made.	
14	10mm Wrench	After all the necessary fuel rail plumbing is installed, reconnect the battery. Cycle the keyed ignition switch ON/OFF a few times (without starting the engine). This allows the fuel pump to prime the system. Check for leaks.	
		Start the engine and confirm again while the engine is running.	
		INSTALLATION COMPLETE	